

Listed in Category Order. Click on an Asset Name for more details.

## Asset Catalog for Packaging (62 Items)

Asset	Description	Condition Location
<b>Agitators</b>		<b>2 Items</b>
<a href="#">Gearbox + Motor 10HP</a> Asset ID: A-1400 United Equipment Technologies	Gearbox and motor - inline. Was originally used for top entering agitator, United Equipment Technologies Model Xcel-22, S/N C1641-7B. Falk right angle gear box. Includes Motor 10HP, 1800 rpm. [Photos of shaft and blades are included for info only to indicate prior service - not available. Shaft diameter : 2.75". Came from 28 ft dia tank x 39 ft tall ] Idled since 2012.	Used - Good Grant City, MO
<a href="#">Gearbox + Motor 15HP</a> Asset ID: A-1306 United Equipment Technologies	Right angle gearbox and motor, for top entering tank agitator. Model XCEL 500. Motor is 15 HP, 1800 rpm. United Equipment Technologies Corp. Includes Falk Right angle gear box. Output 47 rpm. This is gearbox and motor only - used. [Photos of shaft and blades are included for info only to indicate prior service - not available. Shaft diameter : 3.5". Came from 26 ft dia tank x 39.5ft tall ] Idled since 2012.	Used - Good Grant City, MO
<b>Conveyor/Belt</b>		<b>3 Items</b>
<a href="#">Belt Conveyor</a> Asset ID: 2057	Belt conveyor, rubber cleated 23.625" wide. . Includes hopper infeed. Drive motor is 1/2 HP 230/460 3/60 1725 rpm with Nord gaer unit. Built 2019. Part of an entire CBD extraction system - enter PK6020 to see all components.	Used - Very Good Northern US
<a href="#">Belt Conveyor</a> Asset ID: 2359	Belt Conveyor <ul style="list-style-type: none"> <li>• Conveyor length 6'-5" incline with 8" Nose Over</li> <li>• Discharge Height 36" BOF</li> <li>• Incline angle 25 degrees</li> <li>• Belt width 16"</li> <li>• Overall horizontal length 16 feet</li> <li>• Belt: black PVC-120 2-ply with 1/2" tall cleats</li> <li>• Motor 1/2 HP 208-230/460 3/60</li> <li>• Reducer - belt speed 60 fpm fixed</li> <li>• Control panel</li> <li>• Very few hours</li> </ul>	Used - Excellent Tennessee
<a href="#">Belt Conveyor 12ft</a> Asset ID: AF8	Inclined belt conveyor (last used to feed hopper). Approx size 18" wide x 12 ft long.	Unrated Illinois
<b>Electrical</b>		<b>2 Items</b>
<a href="#">Air Core Reactors 2000 KVA</a> Asset ID: B2094 Trench Electric	Air core reactors by Trench Electric, Canada. Dry type, air cooled, rated at 2000 KVA, system volts 13.8 kV, 60 Hz, 1 phase. Rated impedance 0.5 ohm. Built 1993. Serial numbers 117770-4, 117770-3, and 117770-6. Weight 2150 pounds each. Two assembled, one in pieces. Qty (3) - sold as a LOT	Used - Good Peoria, IL

Listed in Category Order. Click on an Asset Name for more details.

<p><a href="#">Disconnect 100HP</a> Asset ID: AF91 Square D</p>	<p>Square D disconnect for 100HP vacuum pumps 460v. Quantity (2) - priced separately.</p>	<p>Illinois</p>
---	---	-----------------

## Electrical/VFD 3 Items

<p><a href="#">VFD 1HP</a> Asset ID: 1459 Automated Direct</p>	<p>Mini VFD drive AC 1HP. Basic scalar control and you want simplicity, the GS1 series can get the job done. Offers an integrated keypad with speed control knob and built-in Modbus communications. Simple volts/Hz control, external analog input 0-10v, 0-20ma, or 4-20 ma. Modbus communications for 230v 3 phase control. Also has speed knob on front.</p>	<p>NEW Cumming, GA</p>
<p><a href="#">VFD 2HP</a> Asset ID: 7016 Allen Bradley</p>	<p>Allen Bradley Adjustable frequency variable speed controller (VFD). Rated for 2 HP. Preset Spd. Series C. Model 160-BA04NPS1. Input 380-460 volts, 3 phase 50/60 hz. Output: 380-460V. Open enclosure IP20 The 160-BA04NPS1 is a Variable Speed Drive. This belongs to the 160 SSC drives by Allen-Bradley. It features compatibility with an input voltage of 380-460 VAC, 3-Phase along with an input current of 4.6 Amperes. It has an output voltage of 380-460 VAC, 3-Phase, output current, and power of 4.0 Amperes and 2.0HP or 1.5 kW, respectively. This drive has an Open (IP20) enclosure and is designed to implement speed modulation via Preset Speed configuration. Quantity (4) - priced separately</p>	<p>Used - Very Good Jacksonville, IL</p>
<p><a href="#">VFD 7.5 HP</a> Asset ID: AF90 SEW</p>	<p>SEW variable frequency drives (VFD) Movidrive. Inverter. SEW part number 08249571. Type MDX61B0055-5A3-4-OT. Size 5.5KW (7.5HP). Input 200-240V with 3HP output. Small footprint 105mm x 314mm weighing 2.8kg. Quantity (10) - priced separately</p>	<p>Used - Good Illinois</p>

## Filters/Bag Filter 4 Items

<p><a href="#">Bag Filter</a> Asset ID: X2089</p>	<p>Bag Filter, quick open top. Specs unknown</p>	<p>Unrated Mississippi</p>
<p><a href="#">Bag Filter 4-bag</a> Asset ID: 2095 FSI</p>	<p><b>Rebuilt FSI 4-Bags design model FSPZ 800-C.S.polishing filter</b></p> <ul style="list-style-type: none"> <li>• Carbon Steel Construction.</li> <li>• 4-Bags Design for N°2 Bag Size.</li> <li>• 4 Strainers Basket in 304 Stainless Steel Construction.</li> <li>• 3" Inlet &amp; Outlet Flanged Connections.</li> <li>• EZ-open lid with hydraulic system.</li> <li>• 800 GPM Maximum Flow Rate. ASME Nat Bd # 2919 MAWP 150 psig @ 400°F. Serial num 46120</li> <li>• Unit is Furnished with 50 Bags. Micron size TBD</li> <li>• Unit Sandblasted, Primed &amp; Painted.</li> </ul>	<p>Reconditioned Texas</p>
<p><a href="#">Bag Filters, Single</a> Asset ID: X2095 Rosedale</p>	<p>Rosedale single bag filter Model 8. New old stock - in warehouse. Carbon steel housing rated at 150 psig. Connection size 2" NPT, Housing size 30 (basket size 30"), swing bolt closure. Takes #2 bags. Fluoroelastomer seal, FSI/Polyloc basket type. Maximum flow rate 220 gpm. Qty (3) - priced separately</p>	<p>New, Old Stock Mississippi</p>
<p><a href="#">Filter Bag</a> Asset ID: H2036</p>	<p>Filter bags for polish filter, size #2. There are 6 boxes of 25 bags each. P2S Polyester Felt Filter Bag. Bags measure 2 ft 5 in long. Priced for the LOT.</p>	<p>New, Old Stock Grant City, MO</p>

Listed in Category Order. Click on an Asset Name for more details.

Filters/Cartridge Filter		3 Items
<a href="#">Cartridge Filters</a> Asset ID: FC-1513	Cartridge filters, stainless steel. Quantity (2) - priced for the set	Grant City, MO
<a href="#">Dust Cartridge Filter 129sf</a> Asset ID: AF11 Wam	Wamflo stainless steel cartridge filter for powder. Type FNC2J12PPOY, serial 11-FN-13-0004866. Size 24" dia x 36" tall on ss skid. Has 8 elements x 920mm long. Filter elements are pleated non-woven polyester. Filter surface area is 12 sq m (129 sf). Self-cleaning - uses compressed air countercurrent cleaning system with timer. Manufactured by Wam.	Illinois
<a href="#">Filter sleeves for cartridge filters</a> Asset ID: H2029 Technologies	Cartridges for cartidge filters. Carbon Blockers made by KX Technologies MatrKX CTO 30 inch cartridges. Model 32-250-125-29. Design is 10 micron, Class 1 Chlorine & Odor & Taste. Diameter 2.5 inches, length 30 inch. Sold 4 to a box - priced per box. Quantity (37) boxes available	Unrated Grant City, MO

Heat Exchanger/Scraped Surface		3 Items
<a href="#">Scraped Surface Heat Exchanger</a> Asset ID: 7145 Votator	Cherry Burrell Votator Scraped Surface Heat Exchanger 6x72 single barrel - Shown As Is but we can recondition if needed. S/N 3455353. Direct Driven by 20HP motor, 1755 rpm/230 rpm out. All wetted surfaces are stainless steel 304, barrel is Chromium plated Nickel. Has 4 rows of ss blades (24 total). MAWP shell 250 psig at 375F/-20F, jacket 150 psig at 375F/-20F. Heat exchange surface area 9 cu ft. Gear reducer Reynold ser No. 3455353, size 5. ratio 7.63:1, output 230 rpm. Volume in tube (product) 880 cu in, volume in jacket 1080 cu in. Physical weight of cylinder & tube is 1100 pounds. Total weight with frame & motor is approx 2500 pounds. Price includes removal & loading on your truck Sold As Is Where Is however, this unit can be reconditioned for additional cost. Cleaned, painted, inspected, new seal, new bearings - 3 month guarantee material and workmanship. New blades and barrel re-chrome are extra options	Used - Fair Grant City, MO
<a href="#">Scraped Surface Heat Exchanger 9sf</a> Asset ID: 7107 Cherry Burrell Votator	Cherry Burrell Votator Scraped Surface Heat Exchanger 6x72 single barrel. Used. Model 1C672L, S/N 35464VA. This unit has a BWS jacket suitable for brine, water, steam. Last use was to cool lecithin edible oil with cooling water. Driven by 20HP motor, 1755 rpm/230 rpm out. All wetted surfaces are stainless steel 304, barrel is Chromium plated Nickel. Has 4 rows of ss blades (24 total). MAWP shell 250 psig at 375F/-20F, jacket 150 psig at 375F/-20F. Heat exchange surface area 9 sq ft. Gear reducer Reynold ser No. 3455353, size 5. ratio 7.63:1, output 230 rpm. Volume in tube (product) 880 cu in, volume in jacket 1080 cu in. Physical weight of cylinder & tube is 1100 pounds. Total weight with frame & motor is approx 2500 pounds. Sold As Is - we can recondition for you for additional. See drawings in LINK. Price includes removal & loading on your truck Sold As Is Where Is however, this unit can be reconditioned for additional cost. Cleaned, painted, inspected, new seal, new bearings - 3 month guarantee material and workmanship. New blades and barrel re-chrome are extra options	Used - Good Ft Worth, TX
<a href="#">Scraped Surface Heat Exchanger 9sf</a> Asset ID: 7108 Votator	Votator Scraped Surface Heat Exchanger 6x72 single barrel. Model 6SSHE, S/N 90294EC, Mfg Number 00-17418, A5136. This unit has a BWS jacket suitable for brine, water, steam. Last use to cool lecithin edible oil with cooling water. All wetted surfaces are stainless steel 304, barrel is Chromium plated Nickel. Has four rows of ss blades (24 total). MAWP tube 400 psi at 375F/-20F, jacket 150 psig at 375F/-20F. Heat exchange surface area 9 cu ft. Volume in tube (product) 910 cu in, volume in jacket 2,000 cu in. Driven by 20HP motor 1755 rpm/222 rpm out Physical weight of cylinder & tube is 1150 pounds. Total weight with frame & motor is approx 2500 pounds. See drawings in LINK. Price includes removal & loading on your truck Sold As Is Where Is however, this unit can be reconditioned for additional cost. Cleaned, painted, inspected, new seal, new bearings - 3 month guarantee material and workmanship. New blades and barrel re-chrome are extra options	Used - Good Ft Worth, TX

Instrument		2 Items
------------	--	---------

# S4M Asset Catalog



Listed in Category Order. Click on an Asset Name for more details.

<a href="#">Dryer Instruments</a> Asset ID: VK-2027	Listing of all instruments on Ring Dryer asset DR-5201. Approximate count 350. See Excel spreadsheet in link. Part of ring dryer DR-5201 and not sold separately at this time. For a list of all components, enter dr5201 in search box.	Unrated Vicksburg, MS
<a href="#">Isolated Signal Converter</a> Asset ID: S2000 Adtech	Adtech powered isolated signal converter, model SCT 502 snap track mounting. Input 4-20 maDC, output 4020 maDC. Power 115 vac. The Adtech Model SCT 502 AC powered Isolated Signal Converter provides a user configurable solution for ground loops and problems encountered in connecting together recorders, process control systems, computers, DCS and PLC systems. The SCT 502 breaks the galvanic path between the transmitted signal and the output receiving device insuring reliable and accurate signal transfer. Qty (10) - priced separately	Used - Very Good Jacksonville, IL

Instrument/plc & HMI		2 Items
<a href="#">AB PanelView 900</a> Asset ID: H2007 Allen Bradley	Allen Bradley Panelview 900. Has 9 inch screen. Cat 2711-K9A2. Series F. Display is AC plasma monochrome 640 x 400 pixel resolution, it has 16 function keys with a keypad operator interface. Serial MK1LN91K, Operator Interface features a DH-485 communication port so the device allows connectivity with an SLC controller, a DH-485 network, a MicroLogix controller, or a Wallmount Power Supply. 100-240 vac 50/60 Hz. Display area 8.27 x 5.17 inches.	Used - Very Good Jacksonville, IL
<a href="#">Starter Panel</a> Asset ID: X2037	Starter and I/O panel, 2-door. Spec unknown - last used as 51A	Unrated Mississippi

Packaging		7 Items
<a href="#">CD Case Feeder</a> Asset ID: E2363 EAM	CD Case Feeder; pneumatic on turn table; Manufactured by EAM	Jacksonville, IL
<a href="#">Chain Wheel Sprocket, Labeler</a> Asset ID: O50 Krones	Chain Wheel / Sprocket 0002091838 1-703-29-038-0 for Krones labeler	New, Old Stock Jacksonville, IL
<a href="#">Dyna Pack (Hot Glue)</a> Asset ID: 6150 ITW Dynatec	ITW Dynatec, Dyna Pack (Hot Glue), 4-line capability currently equipped w/ two (2) programmable heads (6 ft hose, Part # N2306, Serial No. 93468, 230 Volt), TPC-9 controller, Model No. 114231, S.N. 281382, 120-volt 6 Watt (adjustable delay, length of bead, skip, repeat). Was bought new in 2013	Used - Very Good Illinois
<a href="#">Reject Station</a> Asset ID: E2360 Prox switch	Reject Station: Includes Proximity Switch, Air Knife, control box, and tripod stand on wheels - triggers a switch when metal is in close proximity. Last used to detect if CD's were in cases. If a CD was in the case, it would be blown off the line. Includes stand.	Jacksonville, IL
<a href="#">Reject Station Proximity Switch</a> Asset ID: E2361 Turck	Reject Station: Includes Proximity Switch, Air Knife, control box, and tripod stand on wheels - triggers a switch when metal is in close proximity. Proximity switch is Turck BC20-Q20-AN4X2. Last used to detect if CD's were in cases. If a CD was not in the case, it would be blown off the line. Includes stand. Qty (5) of these available, priced separately	Jacksonville, IL

Listed in Category Order. Click on an Asset Name for more details.

<p><a href="#">Shrink Tunnel</a> Asset ID: E2355X Weldotron</p>	<p>Weldotron heat tunnel - Model 7121 S/N FW93271, 220 V, 35 amps, 1 Phase; Motor: 115V, 1 phase, 0.75 amp, 1/15 HP. Dimensions: 74"L x 34"W x 61"H. Tunnel passage width: 16" and height: 8". Versatile shrink tunnel designed to produce complete, uniform shrink on a wide range of product sizes and shapes.</p>	<p>Jacksonville, IL</p>
<p><a href="#">Washers</a> Asset ID: O35 Krones</p>	<p>Krones Foam Washers 1-099-51-076-0 Sold as a Lot of 25</p>	<p>New, Old Stock Jacksonville, IL</p>

Packaging/Bag Inserter		1 Items
<p><a href="#">Bag Inserter</a> Asset ID: 5978 Pearson</p>	<p>Pearson bag inserter - uses poly roll bags. Built 2001. Set up for 50# cube 12" x 12" x 12" box but can be adjusted. Built 2001. Believed to be Model BI-18. Size range L 9.5-24", W 9.5-17", H 10-24". Serial number 200119289647, 3HP 460/3/60. Built 2001. Idled early 2017. Pearson BI18 Bag Inserters open, insert, and cuff plastic bags from roll stock into a wide variety of corrugated cases at speeds up to 18 cases per minute. Equipped with bag opening carriage with vacuum cup assist, four corner cuffing rods and single head bag inserting head, PLC controller, vacuum pump, safety guarding and e-stop. Inserts pre-performed roll stock or gusseted bag stock into cases, filling all corners and cuffing the bag around the outer perimeter. Has a 36" web width with a 1-1/2" diameter spool. Has an Allen Bradley SLC 5/01 PLC. Advanced design features guarantee smooth and precise bag placement and handling. Removed, stored, ready to ship. Part of a complete 50# cube filling line. For a list of all components for this line - enter "5976cube" in search box.</p>	<p>Used - Very Good Jacksonville, IL</p>

Packaging/Case Erector		1 Items
<p><a href="#">Case Erector</a> Asset ID: 5977 Pearson</p>	<p><b>Pearson Case Erector</b></p> <p>Automatic case erector for knock-down (KD) cases with magazine and hot melt bottom glue system. Set up for Left Hand (LH cases) - we have drawing</p> <ul style="list-style-type: none"> <li>• Model CE-235 serial 200102359572, machine number 9572</li> <li>• Rated speeds up to 35 cases / minute.</li> <li>• Feed from right to left when standing in front of machine name and electrical panel</li> <li>• Includes Probilt hot melt glue system, part No. D100-644, serial No. 3551211272</li> <li>• Was erecting KD cases for 50# cubes 12" x 12" x 12" but can be adjusted.</li> <li>• Case size range: Can adjust to handle cases from 5 to 30" long, 5.5 to 16" wide and 3.5 to 24" tall</li> <li>• Driven by 1.5 HP motor 460/3/60</li> <li>• In warehouse - ready to load</li> </ul> <p>Part of a complete 50# cube filling line (Asset 5976) but will be sold separately. Entire line idled in 2017. Removed, stored, ready to ship. For a list of all components for this line - enter "5976cube" in search box. ....</p>	<p>Used - Very Good Jacksonville, IL</p>

Packaging/Case Sealer		2 Items
<p><a href="#">Case Sealer Uncuffer</a> Asset ID: 5980 SV Dice</p>	<p>Case bag uncuffer and sealer. Model PDUC-UFC, sn 4374. Uncuffs poly bag from 50# cube box, folds bag in, tamps it down, and seals top with hot melt glue. Missing hot melt unit and plc from control panel - manufacturer still supports this machine. Part of a complete 50# cube filling line. For a list of all components for this line - enter "5976cube" in search box.</p>	<p>Used - Fair Jacksonville, IL</p>

# S4M Asset Catalog



Listed in Category Order. Click on an Asset Name for more details.

<a href="#">Case Sealer/Taper</a> Asset ID: 6155 Loveshaw Corporation	Case Sealer/Cartron Taper, The Loveshaw Corporation, Model 304/19, S.N. 159183300, 110 Volt, 9.6 Amp. Top & Bottom Sealing Heads, 2 in. x 6 ft. Side Pull Belts, Product Loading "anvil", unit currently has Lincoln Coder, Model 90-2L-I	Unrated
		Illinois

## Packaging/Coder 1 Items

<a href="#">Ink Jet Coder</a> Asset ID: 6158 Videojet	Videojet 1550 (#3), Ink Jet Coding Machine, EXCEL Format, 120/240 Volt, 1Ph., 3 Amp, Serial No. 1404109C29ZH, Part No. 39582-793-01, w/infrared Fiber Optic Photocell (proximity), O.E.M. Mobile Stand, O.E.M. Static Printhead Stand. Running.	Unrated
		Illinois

## Packaging/Complete Line 1 Items

<a href="#">50 lb Cube Filling Line - stainless</a> Asset ID: 5976	Filling line for 50lb cube boxes - stainless steel filler last used for margarine filling. Can be adjusted for other size boxes down to 25 lb. This is an automatic line. Control by Allen Bradley Control Logix plc (filler will have to be re-programmed. Can also be used for shortening filling. Rate was between 5 to 8 cases per minute depending on viscosity (if filling 50# boxes, rate would be 24,000 #/hr). Includes Pearson case erector for LH KD cases, Pearson bag inserter using roll bags, stainless 2-spout filler on Mettler Toledo load cells, and SV Dice uncuffer case sealer (missing plc and hot melt unit). Includes interconnecting conveyors. Line built 2001 - ran until early 2017. Stored in warehouse, ready to load. See marketing flyer. We have a dimension drawing for all major pieces. (5976Layout.pdf). For a list of all components for this line - enter "5976cube" in search box.	Used - Very Good
		Jacksonville, IL

## Packaging/Filler - Fluid 3 Items

<a href="#">Filler - 4 Head Stainless</a> Asset ID: 7621	Bulk viscous material filler - 4 head. For viscous material including shortening and margarine. Stainless steel filler with controls, load cells, and 4 conveyors. Uses 4 Mettler Toledo load cells - controls included. Has 6 automatic ss valves, and 4 conveyor sections on load cells. Can also fill, 25# cube boxes, 50 # cube boxes, 5 gallon (35 lb) pails, 25 kg boxes. Could be adapted for gallon and 1/2 gallon containers and smaller. Stainless so can be used with margarine, butter, or any other viscous product. Ladder logic control included - paper & electronic. Filler control panel measures 3 ft x 7 ft x 1 ft deep. Will have to be reprogrammed. In warehouse - ready to load	Used - Very Good
		Jacksonville, IL
<a href="#">Filler, Viscous Fluid</a> Asset ID: 5942	Filler for 50# cubes - 2 heads. Stainless steel, automatic valves, extrusion valve for shortening or margarine. Two load cells Mettler Toledo, Model IND131, Max load 50kg. Controlled by Allen Bradley touch screen Panelview 1500. Has Allen Bradley Compact Logix plc. Will require re-programming of the logic. Includes Little David Microjet coder and Diagraph IV700 case coder. Capacity 5 to 8 cases per minute depending on viscosity. This is a weigh filler controlled by Mettler load cells. Last used to fill boxes of margarine (12" x 12" x 12") but can handle any viscous fluid. Part of a complete 50# cube filling line. Built 2001. Idled early 2017. Removed, stored, ready to ship. For a list of all components for this line - enter " 5976cube " in search box.	Used - Very Good
		Jacksonville, IL
<a href="#">Pail filler, Liquid - Stainless</a> Asset ID: 7622 Neupak Weigh Master	Neupak Weigh Master Pail Filler, serial # M65301. 2 nozzle Neupak Weighmaster filler for viscous liquids, stainless steel piping and nozzles. Was last used for filling 5 gallon shortening pails but can handle other size pails or boxes. Controls included	Used - Very Good
		Jacksonville, IL

## Packaging/Metal Detector 2 Items

Listed in Category Order. Click on an Asset Name for more details.

<p><a href="#">Metal Detector</a> Asset ID: 6152 LOCK Inspection Systems</p>	<p>LOCK inspection Systems, Met 30+, 3 1/2 in. x 14 in. aperture mounted on conveyor last used with a V/ff/s machine. Conveyor is 12 in x 10 ft. long horizontally-transitioning to 68 inch long incline where the metal detector is located. Intralox modular conveyor belt. Horizontal section is 6 inches above floor and raises to discharge height of 40 inches. Currently using 1.5 MM NFe, 1.2 MM Fe, 2.0 MM SS</p>	Unrated
		Illinois
<p><a href="#">Metal Detector</a> Asset ID: 5072 Eriez Manufacturing Co.</p>	<p>Eriez Flow Through Metal Detector. Model EZ-DSP7.25LPVR, Style 9911198. Serial #191777 Approximate 6" diameter tube with diverter valve. Mounted on a stainless steel frame</p>	Unrated
		Illinois

Packaging/Vertical Form Fill		3 Items
<p><a href="#">Bartelt Form Fill Seal Packager</a> Asset ID: 6125 Bartelt HMC</p>	<p><b>Bartelt Form Fill Seal Packager</b></p> <ul style="list-style-type: none"> <li>Model RH IM 7-12 (7 inch-12 station) w/All Fill B 350E auger filler</li> <li>E.M.P. registration control unit</li> <li>Equipped with side seal embossing and mechanical hole punch</li> <li>Machine No. 580</li> </ul> <p>It has the position for a second filler head. We have run an additional auger filler in that position as well as a volumetric filler in that position. Tear notch and various types auger tooling setups also available separately. Choose from 2 in., 3 1/2 in., 4 in., or 6 in. bag clamps. Very reliable packager. 3 phase 208-220/440 VAC. Selling because of production shut down.</p>	Used - Very Good
		Illinois
<p><a href="#">Bartelt Form Fill Seal Packager</a> Asset ID: 6126 Bartelt HMC</p>	<p><b>Bartelt horizontal form, fill, and seal Packager</b></p> <ul style="list-style-type: none"> <li>Model RH IM 6-7 (6 inch-7 station) w/B Filler</li> <li>Tritronics registration unit (Color Mark II, Model CMS 2B)</li> <li>Last ran 60 packages per minute on 1-gram fill</li> <li>Machine No. 336</li> </ul> <p>Smooth/quiet running machine. 3 phase 208-220 VAC. Selling because of production shut down. Price includes loading on your truck - crating extra. Auxiliary equipment such as embossing and various types auger tooling setups available separately.</p>	Used - Very Good
		Illinois

Listed in Category Order. Click on an Asset Name for more details.

<p><a href="#">Vertical Form Fill Machine (2)</a> Asset ID: 1085 Prodo-Pak</p>	<p><b>TWO Like New Vertical Form Fill &amp; Seal Machines (VFFS)</b></p> <p>by Prodo-Pak. Tested - never used in production. VFF. Selling as a LOT</p> <ul style="list-style-type: none"> <li>LINE 1: One Model 4S 3P 320 line 3-lane with Laser etching printer. Fill rate at 150 to 180 pouches/minute. Size 7.5 ft x 7.5 ft x 9 ft tall 5,000 pounds</li> <li>LINE 2: One Model RV 165 CSW 10 line 10-lane with Laser Jet 3340 printer. Fill rate at 500 to 600 pouches/min. Serial # 8293, unit size 7 ft x 9 ft x 90 inches tall 3,000 pounds.</li> <li>Fill volume 1.0 to 3.0 ml. Pouch width 1.5 inches, pouch length 3.0 inches</li> <li>Both lines were set up for filling semi-viscous gel products 1,000 to 5,000 centipoise into four sided seal pouches. Last used for hand sanitizer packets or sachets.</li> </ul> <p>EACH Line has the following additional pieces:</p> <ul style="list-style-type: none"> <li>Pump skid 80 inch x 48 inch x 60 inch tall 600 pounds</li> <li>Video Jet laser printer 7 ft x 7 ft x 77 inch tall 700 pounds.</li> <li>Video Jet fumes extractor 4 ft x 4 ft x 5 ft tall 300 pounds.</li> </ul> <p>See LINKS for specifications for each line.</p>	<p>Like New</p> <p>New Jersey</p>
--	---	-----------------------------------

Tanks & Pressure Vessels/Pressure Vessel		17 Items
<p><a href="#">Air Receiver</a> Asset ID: X2033 Steelfab</p>	<p>Air receiver pressure tank,carbon steel mfg by SteelFab. ASME NB # 864101 MAWP 165 psig at 400F. Also certified canadian CRN. Must be measured for size - Last certified 2018. Used as East Receiver.</p>	<p>Used - Very Good</p> <p>Mississippi</p>
<p><a href="#">Air Receiver</a> Asset ID: X2061</p>	<p>Vertical carbon steel pressure tank used as VLF Break Tank. ASME stamped pressure vessel. Needs to be measured, specs unknown.</p>	<p>Unrated</p> <p>Mississippi</p>
<p><a href="#">Air Receiver</a> Asset ID: X2108 Steel Fab</p>	<p>Air receiver pressure tank,carbon steel mfg by SteelFab. ASME NB # 864105 MAWP 165 psig at 400F. Also certified canadian CRN. Last certified 2018. Must be measured to verigy specs &amp; nameplate. Used as West Receiver.</p>	<p>Used - Very Good</p> <p>Mississippi</p>
<p><a href="#">Air Receiver Pressure Tank 200 Gallons</a> Asset ID: AF1 Manchester</p>	<p>Air receiver by Manchester Tank. Vertical on base. Size 28" dia x 55: s/s on base for 78" OAH. Capacity 200 gallons. ASME Nat'I Bd # 270535 MAWP 300 psi at 400F. Also CRN certified.</p>	<p>Used - Very Good</p> <p>Illinois</p>
<p><a href="#">Condensate Flash Tank</a> Asset ID: VS-7201 SpecFab</p>	<p>Steam Condensate Flash Receiver mfg by SpecFab. Sn 93x. ASME MAWP 150 psig internal pressure/FV at 400 F. Material carbon steel SA-516-70. Physical size 59" ID x 11' 4" s/s x 0.375 thk. On 5 ft 10" legs. Approx 19 ft 6 in OAH. Insulation 3 inches. Approx capacity 1,937 gallons. Used as Steam Condensate Flash Receiver.</p>	<p>Unrated</p> <p>Vicksburg, MS</p>
<p><a href="#">Condensate Receiver</a> Asset ID: X2042</p>	<p>Condensate receiver. Must be measured but size approx 1.5 ft dia x 8 ft for capacity 100 gallons. Located Next to Control Room</p>	<p>Used - Fair</p> <p>Mississippi</p>



# S4M Asset Catalog



Listed in Category Order. Click on an Asset Name for more details.

<p><a href="#"><u>Condensate Receiver</u></a> Asset ID: VS-4205 Wheeler Tank</p>	<p>Vertical condensate tank on legs mfg by Wheeler tank sn 11746. ASME NB # 15765 MAWP 150 psig at 450F.</p>	<p>Unrated Vicksburg, MS</p>
<p><a href="#"><u>Flash Tank Drum</u></a> Asset ID: 31-V-156 PPV Precision Pipe &amp; Vessel</p>	<p>Steam Flash Drum to atmospheric. Manufactured by Precision Pipe &amp; Vessel in 2009. ASME rated MAWP 150/FV T 250F. Material carbon steel. Part of Absorber &amp; cleanup module FP311</p>	<p>Used - Very Good Soperton, GA</p>
<p><a href="#"><u>Horizontal Decanting Vessel</u></a> Asset ID: V-1506 Confab</p>	<p>Horizontal carbon steel pressure vessel. Decanter and Liquid Knock Out. Built by Confab s/n 64866. ASME Nat'l Bd# 28, rated at 184 psig at 350F (1269 kpa at 177C). Approx size 6.5 ft dia x 18 ft long T/T for 4,468 gallon capacity. Weight: Approx. 12000-15000 lbs. Last used as Decanter in ethanol plant - see schematic link. Insulation has been removed. Price includes removal and loading - ready now to load</p>	<p>Good Grant City, MO</p>
<p><a href="#"><u>Knock Out Pot</u></a> Asset ID: ME-3203 Specfab</p>	<p>Knock out pot Mfg by SpecFab, vertical stainless steel. MAWP 14 psig, Serial number 101. Used as a knock out pot to protect blower BL-3202 CO2 scrubber system. Still installed.</p>	<p>Used - Good Vicksburg, MS</p>
<p><a href="#"><u>Knock Out Pot</u></a> Asset ID: VS-3201 Jogler</p>	<p>Vent Gas Knock-out pot mfg by Jogler. Rated at FV psig external pressure and 50 psig internal pressure at 150 F. Material 304/L SS. Used as vent gas knock out pot. Sn1802268. Part of complete package including blower, pump, structural, see asset PK-3201. For a list of components, enter pk3201 in search on web site.</p>	<p>Used - Good Vicksburg, MS</p>
<p><a href="#"><u>Oil Separator Tank ss</u></a> Asset ID: VS-4204 SpecFab</p>	<p>Vertical stainless steel tank mfg by SpecFab. Size 14" dia x 5 ft s/s for capacity of approx 55 gallons. ASME NB# 72 MAWP 205 psig at 300F. Mfg sn 90. Material SA-312-TP304. See drawing and data sheet in Links. Used as Fusel Oil Separator.</p>	<p>Used - Good Vicksburg, MS</p>
<p><a href="#"><u>Steam Blowdown Drum</u></a> Asset ID: 41-V-630 PPV Precision Pipe &amp; Vessel</p>	<p>Steam drum manufactured by Precision Pipe &amp; Vessel in 2009. ASME MAWP 150 psig/FV at 550F, Nat'l Bd# 893, s/n CV-0893. Material is SA312-TP347. Physical size is 24"dia x 8'-6" s/s, OAH 11'-10" for capacity of 185 gallons. Used as a steam blowdown drum</p>	<p>Used - Very Good Soperton, GA</p>
<p><a href="#"><u>Steam Drum</u></a> Asset ID: 41-V-180 Nebraska Boiler</p>	<p>Steam drum by Nebraska Boiler, built 2009. Horizontal, ASME Nat'l Bd# 877, MAWP 800 psig/FV at 350F, Stainless steel SA-312-304. Physical size 42" dia x 120" s/s x 0.5" shell (11'-3" OAL) for 107cf or 720 gallons. Used as Catalytic Converter steam drum. Part of Catalytic Converter module FP411</p>	<p>Used - Very Good Soperton, GA</p>
<p><a href="#"><u>Sulfur Guard Bed Vessel</u></a> Asset ID: 41-V-196 PPV Precision Pipe &amp; Vessel</p>	<p>Sulfur guard bed vertical vessel. ASME Nat'l Bd 897, MAWP 1650 at 550F, s/n CV-0891 . Mfg by Precision Pipe &amp; Vessel in 2009 - used only 42 days - like new. Material is carbon steel SA-516 70N. Physical size is 4' dia x 14'-4" s/s, approx 23 ft OAH for a capacity of 1410 gallons. Loaded with Haldor Topsoe HTZ-4 sulphur absorption catalyst.</p>	<p>Used - Very Good Soperton, GA</p>
<p><a href="#"><u>Vacuum Pressure Tank</u></a> Asset ID: X2087</p>	<p>Vertical carbon steel pressure tank (vacuum). Need nameplate specs and must be measured but size approx 3 ft dia x 15 ft tall. used as oil dryer</p>	<p>Unrated Mississippi</p>

# S4M Asset Catalog



Listed in Category Order. Click on an Asset Name for more details.

<p><a href="#">Vertical Tanks ss</a> Asset ID: 1966 Tanks USA</p>	<p>Vertical insulated stainless steel tank, working capacity 5,548 gallons (21,000 liters). NEW - still at factory in China. Tank is stainless 316 with insulation and ss304 cladding. Tanks are designed for and built to ASME at an internal design pressure 7.5 bar (112.5 psig) and a working pressure of 6.5 bar (94.25 psig) although they are not certified by ASME. On legs for OAH 7892 mm (25.9 ft). Flange connections are metric 200mm pipe RF flange. Side 500mm manhole. Tanks were for a project that wasn't built. On factory floor now as surplus, ready to ship. Priced as each tank. See tank drawing.</p>	<p>NEW</p>
		<p>China</p>